



INSTALLATION INSTRUCTIONS

NOVA DOCK LEVELER CURTAIN

(Right or left – read from outside facing building)

1. **OPEN UP LEVELER TO FULL HEIGHT:** Use the proper method in securing the leveler in the open position.

NOTE: When installing a Dock Leveler Curtain (DLC) make sure that it does not hinder the leveler function. Also make sure the safety decals are clearly visible. If unable to allow full visibility please contact the OEM for that leveler to get replacement safety decals.

2. **MOUNT VELCRO TO THE LEVELER:** Take the adhesive-backed Velcro and find mounting points on the inside, upper section of the leveler. Small TEK screws may be used for additional support.
3. **ATTACH TOP EDGE OF DLC TO VELCRO:** Using the top Velcro edge on the curtain, attach it to the Velcro on the leveler.

4. **ANCHOR BOTTOM TO THE CURB ANGLE OR CONCRETE:** Use proper mounting method by drilling through the fabric and stay material and anchoring the curtain to the dock.
5. **ATTACH RETRACTOR BUNGIES:** Hook or tie the retractor bungees to un-obstructing parts of the leveler pit and hook them to the curtain grommets. Adjust tension as necessary.
6. **TEST FOR LEVELER FUNCTION:** Ensure the leveler functions properly and the curtain does not get caught in moving parts.

