



1. Product Name

- NOVA NHS Series Hydraulic Dock Leveler
(25,000–40,000 pounds)

2. Manufacturer

NOVA Technology International, LLC
N90 W14507 Commerce Drive
Menomonee Falls, WI 53051

Phone: (262) 502-1591
(800) 236-7325

Fax: (262) 502-1511

Email: sales@novalocks.com
Web: www.novalocks.com

3. Product Description

General Description

NOVA's NHS Series Premium Hydraulic Dock Levelers incorporate the use of hydraulics to raise and lower both the platform and lip. A single push-button activates a hydraulic pump for operating both the leveler platform and lip cylinders. Unit conforms to OSHA, U.S. Department of Commerce Standard CS-202-56 and is manufactured in compliance with the American National Standard of Safety Performance and Testing of Dock Leveling Devices (ANSI) MH 30.1.

Operation

The push-button is depressed and held activating the hydraulic system that lifts the deck from a stored position. When the deck reaches the fully elevated position, the lip cylinder is activated extending the lip assembly. The attendant releases the push-button when the lip is fully extended and the deck descends to the trailer bed. The lip will rest on the trailer bed and the deck will float with the trailer (12 inches above/below dock operating range). After loading/unloading is complete, the attendant depresses the push-button lifting the leveler from the trailer bed. The push-button is held until the lip falls pendant and then released allowing the leveler to rest in the lip keepers.

Structural

The platform is constructed of ¼ inch thick four-way high



tensile 50,000 minimum yield A572 safety tread plate. Platform is reinforced and supported by full length 6 inch high formed C channels welded to deck and front and rear header for firm structural support. Front and rear header plates are ½ inch thick × 7-inches high hot rolled steel. NOVA NHS series lips are four-way safety tread plate, the 25,000 pounds Comparative Industry Rating (CIR) capacity is ½ inch thick, and the 30,000, 35,000 and 40,000 pounds CIR are ⅝ inch thick. The standard lip length is 16 inches on all capacities. Hinge tubes are 1¾ inch OD × ⅝ inch wall, 1⅞ inches OD × ⅜ inch wall or 2⅞ inches OD × ½ inch wall depending on CIR. All lip hinge pins are 1 inch diameter M1044 steel. Steel header gussets are standard on all models 35,000 pounds CIR and above. All units have grease fittings as standard. All platforms are designed to compensate for up to 4 inches of canted trailer bed.

Hydraulics

The platform is raised by a main hydraulic cylinder; all hydraulic hoses are routed under the leveler platform, away from debris. The ramp cylinder is a hard chrome-plated double acting design with a 3-inch bore and is equipped with a velocity safety stop to limit free fall of a loaded platform to 3 inches. Motor pump is mounted up for easy access and to clear debris in pit and includes a translucent reservoir for monitoring fluid level.

Electrical

The hydraulic power unit motor is a 1.25 HP TENV at 120V or 208V single-phase or 208V, 230V, 460V, or 575V three-phase. The electrical control panel is NEMA 12 enclosure. All electrical components, connections and wiring are UL listed or recognized.

Safety Features

A velocity fuse limits the unit to a 1–3-inch drop in a fully loaded free fall situation. Full range telescoping toe guards close off sides even in highest upward position. Built-in maintenance inspection strut that is lockout/tagout compliant is included. Lip keepers are cross-traffic support and serve as automatic night lock security against theft.

Color

Levelers are painted grey.

Dock Bumpers

Two laminated 4-inch 1014 bumpers are standard on the 25,000–40,000 pound CIR units.

Standard Features

- 1¼ HP frame-mounted single- or three-phase motor
- Full-range telescoping toe guards
- Night locks, cross-traffic support
- Integral tamper-proof velocity safety stop
- 16-inch yieldable lip
- Easy clean frame design
- Below dock end load capability
- Positive lip extension and retraction with true regenerative hydraulic control
- NEMA 12 panel
- Two 4-inch 1014 laminated bumpers
- Steel channel deck support members

Optional Features

- Rubber weather seal
- Brush weather seal
- V-112 bumpers
- B-610-14 bumpers
- Three-wheel support
- 18-inch lip
- 20-inch lip
- 5-inch barrier lip (35,000+ pound units only)
- 24-inch riser kit (24-inch pit depth is standard on all 10-foot long levelers)
- Wash down
- 2-inch foam insulation
- Auto-return to dock
- E-stop/independent lip
- NEMA 4 (Push-button box)
- Spray metalized
- Control box stanchion
- Cut down leveler length and width

- Stainless steel pins and lip rods
- Steel pan: 4-sided
- Quick pit: 3-sided

Benefits

- Easy push-button operation for smooth, consistent operation with a hydraulic system that provides for full float at all positions
- Positive lip extension and retraction with true regenerative hydraulic control
- Below-dock end load capability
- Full-width rear hinge mounted in compression with structural channel support
- Velocity fuse hydraulic fail safe stops platform with 1–3-inch in free fall situation
- Subframe design allows for easy quick pit clean out
- Integral maintenance strut is lockout/tagout compliant

Recommended Safety Equipment for Dock Levelers

NOVA Truck Lock and Lock & Load vehicle restraint systems help prevent unexpected trailer departure from the loading dock and minimize trailer creep during the loading/unloading process.

4. Technical Data

Applicable Standards

American National Standards Institute (ANSI)

- ANSI MH30.1-2007—For the Safety, Performance and Testing of Dock Leveling Devices
- ANSI Z535.1—Safety Color Code
- ANSI Z535.3—Criteria for Safety Symbols
- ANSI Z535.4—Product Safety Signs and Labels

American Society for Testing Materials (ASTM)

- ASTM A6/A6M—Standard Specification for General Requirements for Rolled Structural Steel Bars, Plates, Shapes and Sheet Piling
- ASTM A36/A36M—Standard Specification for Carbon Structural Steel
- STM A370—Standard Test Methods and Definitions for Mechanical Testing of Steel Products
- ASTM A786/A786M—Standard Specification for Hot-Rolled Carbon, Low-Alloy, High-Strength Low-Alloy and Alloy Steel Floor Plates
- ASTM D4950—Standard Classification and Specification of Automotive Service Greases

American Welding Society (AWS)

- AWS D1.1—Structural Welding Code—Steel

Military Standards (MIL)

- MIL-L-5606—Performance Specification: Hydraulic Fluid, Petroleum Base; Aircraft, Missile and Ordnance

National Electrical Manufacturers Association (NEMA)

- NEMA 250—Enclosures for Electrical Equipment (1000 Volts Maximum)

National Fire Protection Association (NFPA)

- NFPA 70 National Electric Code (NEC)
- NFPA 79—Electrical Standard for Industrial Machinery

Society of Automotive Engineers (SAE)

- SAE J514—Metallic Tube Connections for Fluid Power and General Use

Underwriters Laboratories, Inc. (UL)

- UL 508 A—Standard for Industrial Control Panel

Environmental Considerations

NOVA Technology uses environmentally-friendly material in its packaging where available.

5. Installation

Unit shipped completely assembled and ready for installation in preformed concrete pit. Pit construction to be in accordance with certified NOVA pit detail drawings.

6. Availability & Cost

Availability

NOVA Technology products and services are sold entirely through the NOVA Nationwide Dealer Network.

For a dealer in your area, routine service, preventative maintenance, product questions, or to request a quote, contact NOVA Technology.

Cost

Pricing information may be obtained from an authorized NOVA dealer.

7. Warranty

In addition to the Standard Product Warranty provided with all NOVA Products, NOVA Technology guarantees materials, components and workmanship to be free of defects for the following extended periods:

Structural Warranty (For levelers with rated capacity of \leq 40,000 pounds CIR)—for a period of five years from the date of shipment, product will carry a prorated structural warranty. This warranty specifically applies to; the deck section, lip section, frame, rear hinge assembly and front hinge assembly only.

Hydraulic Warranty (For levelers with rated capacity of \leq 40,000 pounds CIR)—for a period of five years from date of shipment, product will carry a prorated warranty. This warranty specifically applies to; the hydraulic pump and motor, all hydraulic cylinders, hydraulic pressure lines and fittings only. Complete warranty terms and conditions are available online at www.novalocks.com.

8. Maintenance

Regular maintenance must be performed on a weekly and quarterly schedule. A complete Owner's/User's manual is available online at www.novalocks.com.

9. Technical Services

Technical assistance, including more detailed information, product literature, test results, project lists, or assistance in preparing project specifications, is available by contacting NOVA Technology.

10. Filing Systems

- ARCAT®
- Additional product information is available from the manufacturer upon request